

VFD Utility All In One: MP Mode Command

1. Command List

P07303II_AIO.exe [/a or /p=PORT] [/u=FILE_PATH] [/c=FILE_PATH] [/f=FILE_PATH] [/v]

* []: Necessary

* []: Option

Parameter	Description
/a	Auto-scan serial port to find VFD device. This parameter will take a while to scan device and can't use with "/p" the same time.
/p	Specify serial port to scan. This parameter can't use with "/a" command the same time. Ex: /p=COM1
/u	Update Firmware and specify ebin file path. Ex: /u=c:/temp/test.ebin
/c	Configure VFD Device from file. Ex: /c=C:/temp/Config/4CMVD00V0006.cfg
/f	Update user defined font from file. EX: /f=c:/temp/test.luf
/v	Verify the configuration and firmware version. This parameter will confirm the settings. The settings include configuration and firmware version.
/q	Quit when the MP procedure finish.

2. Example:

The options have order by description above.

EX: P07303II_AIO.exe /a /u=FW/VD00-025.ebin /c=Config/4CMVD00V0006.cfg
/f=Config/03241.luf /v

The example above means steps below.

Step1: auto-scan	Step2: Update Firmware fromVD00-025.ebin
Step3: Setup configurations from 4CMVD00V0006.cfg	Step4: Update user defined font from 03241.luf
Step5: Verify Settings	

